

UPS-Q-LS Series UPS



Standard Features

- 10 to 500 KVA Modules
- Online design provides quality power to your loads at all times
- High Frequency Design for High Efficiency
- True Galvanic Isolation
- Wide Input Range
- Input Surge Protection
- Harsh Environment Tolerance
- Five Stages of Isolation and Conversion
- Pure Sign Wave

Input / Output

Input Voltage:	208/120V, 415/380V, 480/277V
Output Voltage:	Delta: 220V Δ / 380V Δ / 460V Δ Wye: 208VY / 380VY / 400VY / 415 VY
Frequency:	50, 60, 400 Hz

Options

- Emergency Stop Switch
- Remote Control Panel
- Real-time Monitoring Software
- UPQnet-agent II

Specifications

Power Factor:	0.8
Output Waveform:	High Resolution Pure Sine Wave
Single Phase Output:	10 to 50KVA
3 Phase Output:	10 to 500KVA
Output Voltage Regulation:	$\pm 1\%$
Input to Output Isolation:	Dielectric Strength 5KV
Operating Temperature:	0° to 50°C
Humidity:	0% to 90% Non-Condensing
Audible Noise:	< 65 dBA at 1 meter
Approvals:	CSA C22.2, UL 1778, IEEE 587/ANSI 62.41, FCC Class A, EN500091-1, EN500091-2, CE

Mechanical

Dimension :	63"H x 32"D 22"W (10 to 50KVA) 43.5"W (60 to 160KVA) 87"W (240 to 500KVA)
Weight Model Dependant:	551 to 5401 lbs

Available Models

10, 15, 20, 30, 40, 50, 60, 80, 100, 120, 160, 240, 320 and 500 KVA Models.

Warranty

90 days from Manufacture
12 months from RiC

Doc #: BRC-UPS-QLS-01-11-08



RIC ELECTRONICS LTD.
UNIT 130 – 13571 VERDUN PLACE
RICHMOND, B.C. V6V 1W5

PHONE: 604.273-9350
FAX: 604.273.8952
www.ricelectronics.com