

HB4 SWITCH-MODE CHARGER




Standard Features

- Switch-Mode design
- Wide range AC input
- AC Input and DC output breakers
- Back lit 2 line LCD display
- Filtered output for valve regulated batteries
- 4 mode equalize – manual, 30 day, start up and AC fail
- Form C alarm relays.
- Temperature compensation
- MTBF 200,000 hours

Input / Output

Input Voltage (wide range):	85 - 264 VAC (45/65Hz)
Output Voltage:	12V (10A) 24V (2.5/5/10/20A) 48V (2.5/5/10A)

Specifications

Regulation:	+/- 1%
Short Circuit Protection:	Electronically Current Limited
Enclosure:	NEMA 1
Efficiency:	90%
Soft start:	Electronic soft start
Ripple:	50mV
Operation:	-5° to 50° C
Option:	Extended temperature -40° to 55° C
Approvals:	



Settings

Float Voltage:	12V Systems - 11 to 15.7VDC 24V Systems - 22 to 29.2 VDC 48V Systems - 51 to 57.8 VDC
Equalize Voltage:	12V Systems - 11 to 15.7VDC 24V Systems - 22 to 29.2 VDC 48V Systems - 51 to 57.8 VDC
Current Limit:	70 to 115%
Equalize Time:	0 to 24 hours

Alarms

Equalize	Activated by 1 of the 4 equalize modes.
Low Battery Voltage	Below set point for more than 5 seconds
High Battery Voltage	Battery voltage more than .6V above set point
AC Fail	No AC present for more than 5 seconds
Rectifier Fail	Low voltage / low current
Common Alarm	Activated by any of the above alarms

Mechanical

Dimension :	12.2"H x 8.2"W x 7.75"D
Weight:	6.6 to 10.5 lbs depending on model

Available Models

12 Volt:	HB4-12/xx-AB-1 (10)
24 Volt:	HB4-24/xx-AB-1 (2.5/5/10/20)
48 Volt:	HB4-48/xx-AB-1 (2.5/5/10)

Warranty

18 months from date of sale

Doc #: BRC-HB4-1-03-02-09



RIC ELECTRONICS LTD.
UNIT 130 – 13571 VERDUN PLACE
RICHMOND, B.C. V6V 1W5

PHONE: 604.273-9350
FAX: 604.273.8952
www.ricelectronics.com